


= RECOMMENDED FOR MAINTENANCE, REQUIRED FOR COVERS



SPECIFICATIONS & OPTIONS

OPENING SIZE	W=	H=
MFG. DOOR SIZE	W=	H=
PRIMARY VOLTAGE	208-240	440-480 575-600
DRIVE SIDE - (RH / LH)	OPERATOR SPEED = 1	STD.
CONTROL PANEL (ACS 50 / PLC)	SPRINGS	YES
	F.R. COVERS (YES / NO)	
WINDOWS (QTY.) DETERMINED BY MFG. DOOR WIDTH		
FABRIC (BLACK SBR / GRAY EPDM / BLUE EPDM)		
DOOR ACTUATORS (QUANTITY)	PUSHBUTTON	<901>
	PULL SWITCH	<911>
	FLOOR LOOP	<930>
	PHOTOCELLS THRU BEAM	<940>
	MOTION DETECTOR	<950>
	RADIO RECEIVER	<925>
COMMENTS:		

BALANCED / UNBALANCED OVER 24'-0" W x 27'-0" H

CUSTOMER:	APPROVED BY:	
LOCATION:	APPROVED WITH CHANGES BY:	
SALESMAN / DEALER:	DATE: SCALE = N.T.S.	
DESCRIPTION:		
ULTRA TOUGH APPROVAL		
DRAWING NO:	DESIGNER:	DATE:
ULTRA TOUGH-006	JON REITZ	12/07/2007

Rev	Change	Date	Name